



CHRISTRIO

Manufacturer of Beauty Products

1950 Compton Ave. Ste. 103

Corona, CA. 92881

Phone: (951) 808 – 4730 Fax: (951) 808 – 4734

MATERIAL SAFETY DATA SHEET

Section I: Product and Company Identification

Product name: BASIC ONE – Permatop

Chemical Name: N/A

Family Name: UV GELS

Product Use: Professional use only

Product: #4020069

Manufacturer: CHRISTRIO CORP.
1950 Compton Ave. #103
Corona, CA. 92881

Emergency Phone #: 800 535- 5053
International Phone #: 1-352-323-3500
Information Contact: (951) 808 – 4730

Section II: Product composition/Ingredients

Chemical Identity/ INCI Name	CAS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/ OSHA	%
Di-HEMA Trimethylhexyl Dicarbamate	72869-86-4	N/E	N/E	Not Listed	92
Trimethylolpropane Trimethacrylate	3290-92-4	N/E	N/E	Not Listed	5
Benzophenone	119-61-9	N/E	N/E	Not Listed	2
Violet 2/CI60725	81-48-1	N/E	N/E	Not Listed	1

Hazard symbols: Xi, F **Risk Phrases:** R22, R36/37/38, R43 **Safety Phrases:** S18, S24/25, S36/37, S38, S46

N/E – None Established

N/R – Not Reviewed

ND/A – No Data Available

N/A – Not Available

Section III: Hazard Identification

EMERGENCY OVERVIEW

- Flammable Liquid and vapor!
- May be slight toxic.
- May cause chemical burn in eye.
- May cause moderate skin injury (reddening & swelling).

Potential Health Effects, Sign and Symptoms of Exposure:

Primary Route of Entry	No specific information is available.
Eye	No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation
Skin	No specific information available. Skin over exposure or prolonged contact may cause moderate skin injury (reddening and swelling) and/or sensitization in some sensitive of individuals. Since irritation may not occur immediately, contact can go unnoticed.
Ingestion	No specific information available. Contains materials that may practically nontoxic. However, it may cause gastrointestinal irritation with nausea, vomiting and diarrhea.
Inhalation	No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be irritating.
Sub-Chronic effects	No specific information available. Limited tests showed no evidence of teratogenicity in animals. A life time skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for details.

Section IV: First Aid Measure

First Aid for Eye	Flush with plenty of lukewarm water for 15 minutes and seek medical attention immediately.
First Aid for Skin	Remove contaminated clothing and wash contact area with soap and water for 15 minutes. Get medical aid if symptom persisted. Wash clothing before reuse.
First Aid for Inhalation	In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.
First Aid for Ingestion	Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If conscious and alert, rinse mouth and drink 2 to 4 cupfuls of milk or water immediately and seek medical attention.

Section V: Fire fighting Measures
--

Flash Point (°F/°C)	Flammable Limit (Vol %)	Auto-ignition Temperature (Vol %)
>212°F/100°C Setaflash	ND/A	ND/A

Method:

**This product is a combustible liquid. This product may ignite readily and decompose to produce carbon oxides.*

Extinguishing Media:	Use dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.

Unusual Hazards: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

Section VI: Accident Release Measures

Spill or Release Procedure: Small spilled (e.g., <1 gallon). Wear appropriate protective goggles and gloves, remove spill with absorbent materials and place into appropriate closed container for disposal. Large spilled (e.g., >1 gallon). Eliminate all sources of heat and ignition. Use absorbent materials for spill and wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulation (CERCLA) require reporting spills and release to soil, water, and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Section VII: Handling and Storage

Handling: Avoid contact with skin and eyes, and clothing. Use with adequate ventilation and avoid breathing in vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. **Material is extremely light sensitive.** Use extreme care and do not expose to natural or UV light. Unless using material for its purposes. Since the material is very photosensitive any type of light may initiate the hardening (cure) process.

Storage: Store in a tightly closed container. Store in a cool, dry place, away from heat and light. Store at temperatures below 100°F/38°C. Store product in a totally opaque container.

Explosion Hazard: High temperature and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessel or containers.

Section VIII: Exposure Controls/Personal Protective Equipment

Engineering Control

Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

Personal Protective Equipment

General

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash station impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/Face Protection

Wear chemical splash goggles.

Skin Protection

Wear impervious gloves (Neoprene).

Respirator Protection

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Section XI: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Special Gravity	Viscosity	% Volatile
Clear, semi-viscous liquid	Characteristic Acrylate Odor	N/A	(H2O = 1): 1.15	N/DA	By Volume: 0.5

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility in Water (20°C)
Not Applicable	N/A	N/A	(mm Hg) @20°C:0.01	No Data	No Data	No Data	Insoluble
Flash Point (°F/°C)		Flammable Limit (vol%)		Auto-ignition Temperature (vol%)			
>110°F/43°C Penske-Martin		ND/A		ND/A			

Section X: Stability and Reactivity

Stability: Normally Stable

Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.

Hazardous Decomposition Products: Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

Hazardous Polymerization:

May occur—Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Condition to Avoid:

Storage > 100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

Section XI: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation-Skin	Irritation-Eye
ND/A	ND/A	ND/A	ND/A	ND/A

• Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
ND/A	ND/A	ND/A

Section XII: Ecological Information

Acute Toxicity Fish	Acute Toxicity to Invertebrate	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
ND/A	ND/A	ND/A	ND/A	ND/A

Chemical Fate Information

Biodegradability	ND/A
Chemical Oxygen Demand	ND/A

*To be best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.

*Do not allow to entering water supplies, waste water, or soil.

Section XIII: Disposable Concentrations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatsoever, it cannot be save for recovery or recycling should be handle as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from Federal disposal regulations. Dispose of container and unused contents in accordance with Federal, State and local requirements. For EU members, please refer to any relevant Community provision relate to waste. In their absence, it is useful to remind the user that national or regional provision may be in force.

Section XIV: Transport Information

DOT (49 CFR 172)	
Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylate esters), 3, PG III
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	None
Emergency Response Guidebook (ERG) #:	128
IATA (DGR)	

Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl meacrylate, acrylate esters), 3, PG III
Class or Division:	3.2
UN or ID Number:	UN1993
Packaging Instructions:	None
Emergency Response Guidance (ICAO) #:	
IMO (IMDG):	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl meacrlate, acrylate esters), 3, PG III
Class of Division:	3
UN or ID Number:	UN1993
Special Provision & Storage/Segregation:	None
Emergency Schedule (EmS)#:	
Other Information: Flash point >	43°C

Section XV: Regulatory Informatio

Clean Air act: HAP/ODS	This product contains the following Hazardous Air Pollutant (HAP's): <ul style="list-style-type: none"> • None This product does not contains Ozone Depleting Substances (ODS's).
Clean Water Act: Priority Pollutant List	This product contains no chemicals listed under the U.S. Clean Water Act (CWA) This product contains no chemical that are a Priority or Pollutant under Clean Water Act (CWA)
FDA: Food Packaging Status	This product had not been cleared by FDA for use in food packaging and/or other applications an indirect food additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. It's hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
RCRA	This product is not considered to be hazardous waste under RCRA (40 CFR 261). This product is considered to be hazardous waste under RCRA (40 CFR 261) RCRA Code:\ <ul style="list-style-type: none"> • Ethyl Methacrylate, CAS# 97-63-2, RCRA Code: U118 • Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains chemicals regulated under Sec. 302 as extreme hazardous substances that carry TPQ.
SARA Title III: Section 302(RQ)	This product contains chemicals regulated under Sec. 302 as extremely hazardous chemical for emergency release notification ("CERCLA" List). <ul style="list-style-type: none"> • Ethyl Meacrylate, CAS#97-63-2, RQ (lbs): 1000.
SARA Title III: Section 311-312	This product is considered to be hazardous under OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Is hazard are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard

connected with handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only directed. If the product is used as a component of other product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (800) 535-5053.