

MATERIAL DATA SAFETY SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

SECTION I – PRODUCT IDENTIFICATION

REVISION DATE: 12/05/2021

Product Name: GELACQUER PERMASHINE +
 Chemical Name: N/A
 Synonyms: GELACQUER PERMASHINE +
 Trade Name: **GELACQUER PERMASHINE +**
 Product use: Fingernails coating only
 Distributor's Name: CHRISTRIO
 Distributor's Address: 2420 Railroad; Corona, CA. 92881
 Information Contact: 1 951 808 4730
 Emergency Phone: Canada & US (800) 535-5053 International: 1 -352-323-3500
 EU Address: 167-171 Willoughby Lane; Tottenham, London N17 OSB; UK

SECTION II – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information may be based on finding related or similar materials

- May be slightly toxic.
- May cause moderate skin injury (redness & swelling).
- May cause eye irritation

Potential Health Effects, Signs, and Symptoms of Exposure:

Primary Route of Entry	No specific information is available for this product. Although, this product opposes only slight irritation concern with all routes of entry.
Eye	No specific information available. Contains some materials that are essentially nonirritating, however contact may cause slight transient irritation.
Skin	No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.
Ingestion	No specific information available. Contains materials that may be practically nontoxic.
Inhalation	No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be irritating.
Sub-Chronic Effects	No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section XI, Toxicological Information for Details

SECTION III – COMPOSITION/INFORMSTION

Chemical Identity	CAS#	EINEC#	INCI Name	Exposure OSHA TWA/STEL	LIMITS ACGIH TWA/STEL	Carcinogen	%
Polyurethan Acrylate Oligomer	72869-86-4	N/E	Di-HEMA Trimethylhexyl Dicarbamate	N/E	N/E	NOT LISTED	50-60
2-Hydroxyethyl methacrylate	868-77-9	212-782-2	HEMA	N/E	N/E	NOT LISTED	15-20
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	Hydroxypropyl methacrylate	N/E	N/E	NOT LISTED	15-20
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	NOT LISTED	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	NOT LISTED	0-1
TPO	75980-60-8	278-355-8	Trimethylbenzoyl diphenylphosphine oxide	N/E	N/E	NOT LISTED	0-1

See Section XVI for Risk and Safety Phrase

N/E – None Established N/DA – No Data Available N/R – Not Review N/A – Not Applicable

Polyurethane Acrylate Oligomer:	Hazard Symbol: Xi	Risk Phrases: R36/37/38	Safety Phrases: S14, S3/7, S62
2-Hydroxy ethyl methacrylate:	Hazard Symbols – Xi	Risk Phrases – R36/38, R43	Safety Phrases – S2, S26, S28
Hydroxypropyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36/37/38, R43	Safety Phrases: S26, S36/37
TPO:	Hazard Symbol:	Risk Phrases: R99	Safety Phrases:

MATERIAL DATA SAFETY SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

First Aid for Eye	Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention immediately.
First Aid for Skin	Remove contaminated clothing and wash contact area with soap and water for 15 minutes.
First Aid for Inhalation	In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.
First Aid for Ingestion	If appreciable quantities are swallowed seek emergency medical attention.

Flash Point (°F/°C)	Flammable Limit (vol %)	Auto-Ignition Temperature (vol %)
>212°F/100°C	N/D	N/D

Spill or Release Procedures	Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well-ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.
-----------------------------	---

Handling	Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheating of product, this will also diminishing the quality of the product.
Storage	Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.
Explosion Hazard	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessel

MATERIAL DATA SAFETY SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Personal Protective Equipment General Eye/Face Protection Skin Protection Respiratory Protection	Local exhaust recommended control exposure, which may result from operations generating aerosols and hot operations generating vapors. To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole suit. Nitrile rubber is better PVC. Chemical splash goggles. Impervious gloves (Neoprene). A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances, where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR1910.134 or European Standard EN149.
--	--

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Odor & Odor Theshold	pH	Specific Gravity	Viscosity	% Volatile
Clear to slight violet, viscous liquid	Characteristic acrylate odor	N/A	(H2O=1) : 1.15	N/DA	By Volume:<.5

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solution In Water
N/A	N/A	N/A	(mm Hg) @ 20 C:<0.01	N/D	N/D	N/D	Insoluble

Flash point (°F/°C)	Flammable Limit (Vol %)	Auto-ignition Temperature (Vol %)
>212 °F/100°C Setaflash	N/D	N/D

SECTION X - STABILITY AND REACTIVITY

Stability: Normally Stable	Incompatibility (Materials to Avoid): Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.
Hazardous Decomposition Products: Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.	Hazardous Polymerization: May occur -- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Conditions to Avoid:

Storage > 100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitore, contamination with incompatible materials.

SECTION XI - TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - Skin	Irritation -Eye
N/DA	N/DA	N/DA	N/DA	N/DA

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

MATERIAL DATA SAFETY SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

SECTION XII - Ecological Information

Ecotoxicological Information

Acute Toxicity To Fish	Acute Toxicity To Ivertebrates	Acute Toxicity To Algea	Bioconcentration	Toxicity to Sewage Bacterials
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been investigated. DO NOT allow to entering drinking water supplies, wastewater, or soil.

SECTION XIII- DISPOSAL CONSIDERATIONS

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all Federal, State, and local regulations. Disposal of diking materials and absorbent in compliance with State, Local, and Federal regulations. When large amount of product use. Residue vapors may explode on ignition; DO NOT cut, drill, or well on or near the container. Mix with compatible chemical which is less flammable and incinerate.

SECTION XIV - TRANSPORT INFORMATION

DOT (49 CFR 172) (GND)	
Proper Shipping Name	Non-Regulated Material
Identification	N/A
Marine Pollutant	No
Special Provisions	None
Emergency Response Guidebook (ERG) #	N/A
IATA (DGR) (AIR)	
Proper Shipping Name	Non-Regulated Material
Class or Division	N/A
UN or ID Number	N/A
Packing Instructions	None
Emergency Response Guidance(ICAO)#	N/A
IMO (IMDG)	
Proper Shipping Name	Non-Regulated Material
Class or Division	N/A
UN or ID Number	N/A
Special Provision & Stowage/Segregation	None
Emergency Schedule (EmS)#	N/A
Other Information	Flash point >100°C

SECTION XV - REGULATORY INFORMATION

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> • Acrylic Acid, CAS# 79-10-7(HAP) This product contains no ODS's
Clean Water Act: Priority Pollutant	This product no chemical listed under the U.S. Clean Water Act Priority Pollutant List.
FDA: Food Packing Status	This product has not been cleared by the FDA for use in food packaging and/or other application as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Satandard. Its hazards are: *Immediate (acute) health hazard *Delayed (chronic) health hazard *Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).

MATERIAL DATA SAFETY SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

SECTION XV – REGULATORY INFORMATION (Continued)

SARA Title III: Section 311-312	This product is considered hazardous under OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazard are: *Immediate (acute) health hazard *Delayed (chronic) health hazard *Reactive hazard
SARA Title III: Section 313	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule	None of the chemicals listed have a SNUR under TSCA.


State Regulation

CA Right-to-Know Law California No Significant risk Rule	None None
MA Right-to-Know Law	This product contains the following hazardous component subject to disclosure under MA Right-to-Know legislation: NONE
NJ Right-to-Know	This product contains the following hazardous component subject to disclosure under NJ Right-to-Know legislation: NONE
PA Right-to-Know Law	This product contains the following hazardous component subject to disclosure under PA Right-to-Know legislation: NONE
FL Right-to-Know Law	This product contains the following hazardous component subject to disclosure under FL Right-to-Know legislation: NONE
MN Right-to-Know Law	This product contains the following non-hazardous components subject to disclosure under MN Right-to-Know legislation: NONE

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS = n/da 2-Hydroxyethyl methacrylate CAS# 868-77-9 is on the DSL List. WHMIS = n/da
---	--

Labeling according to directive – 1999/4/EC

European Community: 	BASIC ONE Sculpture Clear Gel <ul style="list-style-type: none"> HAZARD SYMBOLS: Xi: Irritant RISK PHRASE: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact. SAFETY PHRASE: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment.
---	--

SECTION XVI – OTHER INFORMATION


EU Class and Risk/Safety Phrases for Referenced Ingredients (See Section 2):

<p>Hazard Symbol: Xi – Irritants</p> <p>Risk Phrases: R36/37/38 Irritating to eyes, respiratory system and skin; R35 Causes severe burns; R43 May cause sensitization by skin contact;</p> <p>Safety Phrases: S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S28 After contact with skin, wash immediately with plenty of water; S36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label</p>
--

MATERIAL DATA SAFETY SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

Hazard Rating system (Pictograms)

<p>NFPA:</p> 	<p style="text-align: right;">HMS:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="background-color: blue; color: white; text-align: center;">2</td><td style="background-color: blue; color: white;">HEALTH</td></tr> <tr><td style="background-color: red; color: white; text-align: center;">1</td><td style="background-color: red; color: white;">FLAMMABILITY</td></tr> <tr><td style="background-color: yellow; color: black; text-align: center;">1</td><td style="background-color: yellow; color: black;">REACTIVITY</td></tr> <tr><td style="background-color: white; height: 20px;"></td><td></td></tr> </table>	2	HEALTH	1	FLAMMABILITY	1	REACTIVITY		
2	HEALTH								
1	FLAMMABILITY								
1	REACTIVITY								

N/E - Not Establish N/R - No Review N/DA - No Data Available N/A - Not Applicable
 OSHA PEL for nuisance dust 15mg/m³ (total dust) 5mg/m³ (Respirable dust)
 ACGIH PEL for nuisance dust 10mg/m³

Prepared By:	CHRISTRIO
Update Composition	May 12 th , 2021

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended to use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expenses arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained with this MSDS may not applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1 (800) 535-5053.

CHRISTRIO products are provided on an as is basic without warranties of any kind either expressed or implied. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said CHRISTRIO products. It is the sole responsibility of the user to examine and determine appropriate application and requirements associated with said CHRISTRIO components.